



Model (型式)	Orifice Size (オリフィスサイズ)	Max. Differential Press. (最高作動圧力差)
1010-1.4	3/16 (4.8 mm)	0.14 MPa
1010-5.6	1/8 (3.2 mm)	0.56 MPa
1010-8.7	7/64 (2.8 mm)	0.87 MPa
1010-10.5	#38 (2.5 mm)	1.05 MPa
1011-1.0	1/4 (6.4 mm)	0.10 MPa
1011-2.1	3/16 (4.8 mm)	0.21 MPa
1011-4.9	5/32 (4.0 mm)	0.49 MPa
1011-8.7	1/8 (3.2 mm)	0.87 MPa
1011-14	7/64 (2.8 mm)	1.40 MPa
1011-17.5	#38 (2.5 mm)	1.75 MPa
1011-28	5/64 (2.0 mm)	2.80 MPa
1022-1.0	5/16 (7.9 mm)	0.10 MPa
1022-2.1	1/4 (6.4 mm)	0.21 MPa
1022-4.9	3/16 (4.8 mm)	0.49 MPa
1022-8.7	5/32 (4.0 mm)	0.87 MPa
1022-14	1/8 (3.2 mm)	1.40 MPa
1022-21	7/64 (2.8 mm)	2.10 MPa
1022-45	#38 (2.5 mm)	4.50 MPa
1013-1.0	1/2 (12.7 mm)	0.10 MPa
1013-2.1	3/8 (9.5 mm)	0.21 MPa
1013-4.2	5/16 (7.9 mm)	0.42 MPa
1013-5.6	9/32 (7.1 mm)	0.56 MPa
1013-8.7	1/4 (6.4 mm)	0.87 MPa
1013-12.6	7/32 (5.6 mm)	1.26 MPa
1013-17.5	3/16 (4.8 mm)	1.75 MPa
1013-31.5	5/32 (4.0 mm)	3.15 MPa

* 型式により形状が異なります。

Name of Parts	Material	部品名	材質	Q.TY
6 Bucket	Stainless Steel	バケット	ステンレス鋼	1
5 Leverage System	Stainless Steel	レバー機構	ステンレス鋼	1 set
4 Valve	Heat Treated Chrome Steel	弁体	焼入れクローム鋼	1
3 Valve Seat	Heat Treated Chrome Steel	弁座	焼入れクローム鋼	1
2 Connections	Stainless Steel	接続継手	ステンレス鋼	2
1 Body	Stainless Steel	本体	ステンレス鋼	1

Model	Size	d	A	H	K	Weight
1010	15A	Rc 1/2	70	154	14	0.6
	20A	Rc 3/4	70	154	14	0.7
1011	15A	Rc 1/2	70	184	14	0.7
	20A	Rc 3/4	70	184	14	0.8
1022	20A	Rc 3/4	100	225	18	2.0
1013	25A	Rc 1	114	289	30	3.4

Specification	
Fluid	
Press.	MPa
Temp.	

TYPE 1010 SERIES STEAM TRAP
スチームトラップ

Approval	M. KUME
Check	T. SHINJO
Drawing	K. YASUDA
Drawing No.	Y-409-3601
Date	22 APR. 2007

