



\*製品に流れ方向の制約はありません。

(mm)								
Size	S	d	L	h <sub>1</sub>	h <sub>2</sub>	H	Weight (kg)	Actuator
15A	Rc 1/2	13	59	36	58	121	1.3	AM1-030
20A	Rc 3/4	16	66	36	58	123	1.4	AM1-030
25A	Rc 1	20	78	36	58	129	1.6	AM1-030
32A	Rc 1 1/4	25	87	36	58	140	2.0	AM1-070
40A	Rc 1 1/2	32	95	36	58	146	2.3	AM1-070
50A	Rc 2	39	109	53	85	194	3.4	AM1-180

\*ケーブルコネクタの適合ケーブル外径はφ5~10.5

No	Name of Parts	Material	部品名	材質	Q. TY
9	Cable Conector	NYLON	電線コネクタ	ナイロン	1
8	Actuator	Aluminium/PC	電動操作機	ADC/PC	1
7	Conector	Stainless Steel	コネクタ	SUS304	1
6	O Ring	NBR	Oリング	NBR	1
5	O Ring	FKM	Oリング	FKM	1
4	Stem	Stainless Steel	ステム	SUS316	1
3	Seat	PTFE	シート	PTFE	2
2	Ball	Stainless Steel or Cast Stainless Steel	ボール	SUS316 or SCS14A	1
1	Body	Cast Stainless Steel	本体	SCS14A	1

Specification	
Fluid	
Press.	MPa
Temp.	℃
Rate Voltage	AC100/110V AC200/220V

TYPE MD-53 TWO WAY MOTOR VALVE  
電動二方弁

Approval	H. Iwamoto
Check	T. Watanabe
Drawing	Y. Morita
Drawing No.	Y-984-3601-1C
Date	29 DEC. 2020

