



40~50A

6	Label	Polyester	日本水道協会 品質認証センター 認証ラベル	ポリエステル	1
5	Plug	Stainless Steel	プラグ	SUS	1
4	Screen	Stainless Steel	スクリーン	SUS304	1
3	Gasket	PTFE	ガスケット	PTFE	1
2	Cap	Bronze	キャップ	CAC406	1
1	Body	Bronze	本体	CAC406	1
No.	Name of Parts	Material	部品名	材質	Q. TY

Size	d	L	H <sub>1</sub>	ls	ds	Plug	Weight (kg)
15A	Rc 1/2	86	55	35	20	—	0.5
20A	Rc 3/4	98	70	50	25	—	0.8
25A	Rc 1	117	80	60	32	—	1.1
32A	Rc 1 1/4	145	92	70	40	—	1.9
40A	Rc 1 1/2	148	105	75	45	R 3/8	2.6
50A	Rc 2	178	122	90	56	R 3/8	3.8

Specification	
Fluid	
Press.	MPa
Temp.	℃
Flow Rate	
Inside Screen	Mesh
Outside Screen	∅ - ㄱ/cm <sup>2</sup>

TYPE SY-6-N STRAINER  
ストレーナ

Approval	H. Iwamoto
Check	H. Kamada
Drawing	K. Takenaka
Drawing No.	Y-1237-1401-1A
Date	31 OCT. 2016

**Yoshitake**  
INC.