



Model (型式)	Orifice Size (オリフィスサイズ)	Max. Differential Press. (最高作動圧力差)
TB-812- 1.0	5/16 (7.9mm)	0.10 MPa
TB-812- 2.1	1/4 (6.4mm)	0.21 MPa
TB-812- 4.9	3/16 (4.8mm)	0.49 MPa
TB-812- 8.7	5/32 (4.0mm)	0.87 MPa
TB-812- 14	1/8 (3.2mm)	1.40 MPa
TB-812- 16	7/64 (2.8mm)	1.60 MPa

14	Rivet	Stainless Steel	打込みねじ	SUS304	1
13	Name Plate	Stainless Steel	銘板	SUS304	1
12	Plug	Carbon Steel	プラグ	AISI1008-1010	1
11	Bolts & Nuts	Carbon Steel	ボルト・ナット	ASTM B633 TYPE1	1set
10	Guide Pipe	Stainless Steel	パイプノック	SUS304	1
9	Gasket	Non Asbestos	ガスケット	G#3400	1
8	Plug	Carbon Steel	プラグ	AISI1008-1010	1
7	Pipe	Carbon Steel Pipe	入口案内管	ASTM A53	1
6	Lever	Stainless Steel	レバー	ASTM A240 304	1
5	Bucket	Stainless Steel	バケット	ASTM A240 304	1
4	Valve Seat	Stainless Steel	弁座	ASTM A582 440F	1
3	Valve	Stainless Steel	弁体	ASTM A582 440F	1
2	Cover	Cast Iron	ふた	ASTM A48 Class 30	1
1	Body	Cast Iron	本体	ASTM A48 Class 30	1
No.	Name of Parts	Material	部品名	材質	Q. TY

TYPE TB-812 STEAM TRAP
スチームトラップ

Approval	M. Kume
Check	Y. Aoyama
Drawing	S. Kanematu
Drawing No.	Y-354-0801
Date	26 JAN. 2011



(mm)								
Size	d	L	H	H ₁	A	Plug No. 8	Plug No. 12	Weight (kg)
15A	Rc 1/2	165	230	137	143	NPT1/2	NPT1/2	6.8
20A	Rc 3/4	165	230	137	143	NPT1/2	NPT1/2	6.8

Specification	
Fluid	
Press.	MPa
Temp.	°C