



Model (型式)	Orifice Size (オリフィスサイズ)	Max. Differential Press. (最高作動圧力差)
TB-815- 1.0	3/4	0.10 MPa
TB-815- 2.1	9/16	0.21 MPa
TB-815- 4.2	7/16	0.42 MPa
TB-815- 7.0	3/8	0.70 MPa
TB-815- 8.7	11/32	0.87 MPa
TB-815-12.6	5/16	1.26 MPa
TB-815- 16	1/4	1.60 MPa

※With Weight (Cast Iron)

13	Name Plate	Stainless Steel	銘板	SUS304	1
12	Plug	Carbon Steel	プラグ	AISI1008-1010	1
11	Bolts & Nuts	Carbon Steel	ボルト・ナット	ASTM B633 TYPE1	1set
10	Guide Pipe	Stainless Steel	パイプノック	SUS304	1
9	Gasket	Non Asbestos	ガスケット	Non Asbestos	1
8	Plug	Carbon Steel	プラグ	AISI1008-1010	1
7	Pipe	Carbon Steel Pipe	入口案内管	ASTM A53	1
6	Lever	Stainless Steel	レバー	ASTM A240 304	1
5	Bucket	Stainless Steel	バケット	ASTM A240 304	1
4	Valve Seat	Stainless Steel	弁座	ASTM A582 440F	1
3	Valve	Stainless Steel	弁体	ASTM A582 440F	1
2	Cover	Cast Iron	ふた	ASTM A48 Class 30	1
1	Body	Cast Iron	本体	ASTM A48 Class 30	1
No.	Name of Parts	Material	部品名	材質	Q. TY

Size	d	L	H	H ₁	(mm)			Weight (kg)
					⊘A	⊘8 Plug	⊘12 Plug	
32A	Rc 1 1/4	260	413	205	229	NPT1 1/2	NPT1 1/2	32.2
40A	Rc 1 1/2	260	413	205	229	NPT1 1/2	NPT1 1/2	32.2
50A	Rc 2	260	413	205	229	NPT1 1/2	NPT1 1/2	32.2

Specification	
Fluid	
Press.	MPa
Temp.	℃

TYPE TB-815 STEAM TRAP
スチームトラップ

Approval	H. Iwamoto
Check	Y. Aoyama
Drawing	S. Kanematsu
Drawing No.	Y-354-0801-6A
Date	22 JUL. 2015

