



Shipping Boltは、配管(固定点及びガイド施工)後取り外しの事。
 Be sure to remove the Shipping Bolt after installation(Fixing point and guide execution).

Specification	
Fluid	
Max.Press.	MPa
Max.Temp.	
Expansion Amt.	+ 10, - 35 mm

15	Bolt Holder	Rolled Steel	ボルトホルダー	SS400	3
14	Shipping Bolt	Rolled Steel	SHIPPING ボルト	SS400	3set
13	Guide Pipe	Carbon Steel Pipe or Rolled Steel	ガイドパイプ	SGP or SS400	1
12	Sleeve	Stainless Steel	スリーブ	SUS316L	1
11	Ring	Rolled Steel	リング	SS400	1
10	Support	Rolled Steel	肩当	SS400	1
9	Cover	Rolled Steel	カバー	SS400	1
8	Inside Pipe	Stainless Steel	内筒	SUS316L	1
7	Control Ring	Rolled Steel	コントロールリング	SS400	7
6	Bellows	Stainless Steel	ベローズ	SUS316L	1
5	Support	Rolled Steel	肩当	SS400	1
4	Sleeve	Stainless Steel	スリーブ	SUS316L	1
3	Guide Pipe	Carbon Steel Pipe or Rolled Steel	ガイドパイプ	SGP or SS400	1
2	Flange	Rolled Steel	フランジ	SS400	2
1	Packing Seat	Stainless Steel	パッキンシート	SUS316L	2
No.	Name of Parts	Material	部品名	材質	Q.TY

Size	L	使用最大長さ Max. Operating Length	使用最小長さ Min. Operating Length	最大伸縮長さ Max. Expansion Length	D0	d	G	Flange JIS 10K FF				Weight (kg)
								D	C	t	n-h	
300A	510	520	475	45	391.4	295	368	445	400	24	16-25	113
350A	510	520	475		441.4	330	413	490	445	26	16-25	143
400A	510	520	475		491.4	385	475	560	510	28	16-27	168
450A	510	520	475		541.4	435	530	620	565	30	20-27	193

TYPE EB-3 EXPANSION JOINT
 伸縮管継手

Approval	M. Kume
Check	H. Tange
Drawing	T. Shinjo
Drawing No.	Y-0090-6005
Date	29 OCT. 2004

