



単位 : mm

呼び径	ゴム本体			フランジ				許容変位量				最高 使用圧力 (MPa)	試験 圧力 (MPa)							
	L	A	G	T	D	C	N-φH	偏心	伸長	圧縮	偏角									
20A	150	17	49	14	100	75	4-15	10	5	10	15°	1.0	1.5							
25A		23	61		125	90														
32A		37	69		135	100														
40A		16	48	86	140	105	4-19													
50A			63	106	155	120														
65A			76	116	175	140														
80A		18	100	150	185	150	8-19													
100A			124	180	210	175														
125A			280	240	8-23															
150A	150	149	209	22	280	240	8-23	25	20	15										
	200							20												
200A	150	195	260	24	330	290	12-23	20	15	15										
	200																			
250A	200	242	320	24	400	355	12-25	25	15	20	15°	1.0	1.5							
300A		284	367		445	400														
350A		325	420		490	445														
400A		26	383	471	560	510	16-25													
450A			436	519	620	565														
500A			475	569	675	620														
					30	620	565							20-27					0.5	0.75

⑤	補強コード	合成繊維		名称	合成ゴム製防振継手				
④	外面ゴム	合成ゴム	EPDM	型式	S-FLEX			JIS10K 相当	
③	内面ゴム	合成ゴム	EPDM		作図	K.I	検図	K.I	承認
②	補強リング	SWRH		図番		12032-8		作成日	19.11.20
①	フランジ	SS400	ユニクロめっき						
記号	名称	材質	備考	株式会社アトムズ					